

# OTDR Report (1310 nm (9 μm))

## General Information

File name:	20_1310.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	4:31 PM	Fiber ID:	20
Cable ID:	FAR5 to SS6A (C) B (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


## Locations

	Location A	Location B
Location	SS6A	FAR5
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

## Results

Span length:	1.1480 km	Average loss:	0.703 dB/km	Injection level:	25.4 dB
Span loss:	0.807 dB	Average splice loss:	---		
Span ORL:	39.46 dB	Maximum splice loss:	---		

## Graph



## Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.923 dB/km	A-B average loss:	-7.390 dB/km
a	0.0000	25.418	A-B LSA loss:	1.062 dB	4-point Event Loss:	-8.903 dB
A	0.0000	25.418	A-B ORL:	37.78 dB	Maximum reflectance:	-43.5 dB
B	1.1502	33.918				
b	1.1502	33.918				

# OTDR Report (1310 nm (9 μm))

## Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0567	0.361		0.341	0.361
Reflective	2	1.0567	0.401	-57.5		0.762
Section		0.0913	0.045		0.497	0.807
Reflective	3	1.1480	---	> -23.8		0.807

## Macrobend

Position (km)	Delta Loss (dB)

## Pass/Fail Thresholds

	1310 nm (9 μm)

## Test Parameters

	A → B
Wavelength (nm)	1310 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

## Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.467700		
Backscatter (dB)	-79.45		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		

# OTDR Report (1550 nm (9 μm))

## General Information

File name:	20_1550.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	4:31 PM	Fiber ID:	20
Cable ID:	FAR5 to SS6A (C) B (B-A)		
Job ID:	0500831		
Comments:	END TO END TEST		


## Locations

	Location A	Location B
Location	SS6A	FAR5
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

## Results

Span length:	1.1478 km	Average loss:	0.455 dB/km	Injection level:	24.2 dB
Span loss:	0.522 dB	Average splice loss:	---		
Span ORL:	41.64 dB	Maximum splice loss:	---		

## Graph



## Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.792 dB/km	A-B average loss:	-8.284 dB/km
a	0.0000	24.702	A-B LSA loss:	0.911 dB	4-point Event Loss:	-9.758 dB
A	0.0000	24.702	A-B ORL:	39.19 dB	Maximum reflectance:	-42.7 dB
B	1.1502	34.230				
b	1.1502	34.230				

# OTDR Report (1550 nm (9 μm))

## Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0566	0.199		0.188	0.199
Reflective	2	1.0566	0.315	-57.3		0.514
Section		0.0912	0.008		0.088	0.522
Reflective	3	1.1478	---	> -24.2		0.522

## Macrobend

Position (km)	Delta Loss (dB)

## Pass/Fail Thresholds

	1550 nm (9 μm)

## Test Parameters

	A → B
Wavelength (nm)	1550 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

## Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.468325		
Backscatter (dB)	-81.87		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		